

# SCAT TRAK<sup>®</sup>

## SKID STEER LOADERS

1300D  
1500D  
1500DX  
1750D  
2000D  
2000DX  
2300D  
2300DX

## SKID STEER LOADERS

### High Performance

- ▶ High breakout force and axle torque
- ▶ Powerful hydraulic pump for fast cycle times, more power to run optional attachments

### Operator Comfort

- ▶ Extra wide operator compartment
- ▶ Convenient hand and foot controls standard (wrist action controls optional)
- ▶ Easy entrance and exit
- ▶ Easy to read gauge/warning light panel

### Easy Access

- ▶ Forward tilting ROPS/FOPS cab allows quick and easy access to engine/hydrostatic and hydraulic components



Model	1300D	1500D	1500DX	1750D	2000D	2000DX	2300D	2300DX
Operating Capacity	1350 lb (612 kg)	1500 lb (680 kg)	1500 lb (680 kg)	1875 lb (851 kg)	2000 lb (908 kg)	2000 lb (908 kg)	2450 lb (1112 kg)	2450 lb (1112 kg)
Engine	Kubota/49.5 HP (36,9 kW)	Kubota/60 HP (44,7 kW)	Kubota/60 HP (44,7 kW)	Perkins/86 HP (64 kW)	Perkins/86 HP (64 kW)	Perkins/86 HP (64 kW)	Perkins/86 HP (64 kW)	Perkins/86 HP (64 kW)
Hydraulic Flow	16.4 GPM (62 l/min)	16.4 GPM (62 l/min)	31 GPM (117 l/min)	19 GPM (72 l/min)	19 GPM (72 l/min)	33 GPM (124,9 l/min)	22 GPM (83 l/min)	33 GPM (124,9 l/min)
Bucket Width	60" (1524 mm)	66" (1676 mm)	66" (1676 mm)	72" (1829 mm)	72" (1829 mm)	72" (1829 mm)	72" (1829 mm)	72" (1829 mm)
Height to Hinge	113" (2870 mm)	113.8" (2891 mm)	113.8" (2891 mm)	121" (3073 mm)	121" (3073 mm)	121" (3073 mm)	121" (3073 mm)	121" (3073 mm)



Powerful hydraulic pump provides plenty of power for optional attachments.



The in-line loader linkage provides excellent bucket visibility.



A wide range of versatile attachments are available.