

BM·VOLVO

DUMPER DR 631



- Articulated steering, 4-wheel drive, built for driving both on and off the road
- 10-ton load capacity
- Big--85° --tip angle
- Rugged axles with differential lock; rear axle incorporates hub reduction
- Roomy, well-insulated cab, tested for impact resistance: truck-type driver's seat
- Big wheels, tight turning circle: never-get-stuck performance

Technical particulars

General

Tare weight	8 tons
Payload	10 "
Length	7.65 m (300 in.)
Width	2.5 m (98 1/2 in.)
Body-side height	2.2 m (86 1/2 in.)
Max. steering angle	45°
Tip angle	85°
Load capacity, struck vol., with tailgate	5.4 cu.m. (7 cu.yd.)

Engine

Diesel, type	BM 1113 TR
Rating at 2000 r.p.m.	65 h.p. SAE
Max. torque at 1,400 r.p.m.	24.5 kgm (177 ft-lb.)

Hydraulics

Pump	Vickers 25 V 14 A - 6A 10 L
Working pressure	120 kg/cm ² (1,707 psi)
Capacity at 1,500 r.p.m. (engine)	57 l/min. (12 1/2 Imp.gpm)

The manufacturers reserve the right to change specifications without prior notice.

Gearbox

10 speeds forward, 2 in reverse	
Speed range forward, gears 1-10	2.8-25.8 k.p.h. (1.7-16 m.p.h.)
Speed range in reverse, low/high	3.7/4.7 k.p.h. (3/4 m.p.h.)

Brakes

Mechanical, on front section	755 sq.cm. (117 sq.in.)
Pneumatic/mechanical, on rear section	2,675 sq.cm. (414 sq.in.)

Tyres

Front	18.4-34/14
Rear	16.00-24/12

Electrical

System	Bosch 12 V
Battery capacity	152 Ah
Generator rating	130 W
Starter rating	4 h.p.

Optional equipment

Top-hinged tailgate	
Heavy duty rock body	



BOLINDER-MUNKTELL

a member of the Volvo Group, Eskilstuna, Sweden.