

Volvo Construction Equipment
Building Tomorrow



A60H

Volvo Articulated Haulers 55 t 673 hp



Pure uptime

Get continuous production with this bigger, durable and superior machine – always available and ready to work. Count on superb reliability thanks to the machine's robust design, easy service access and outstanding Volvo dealer network. Guarantee pure uptime.

Guaranteed durability

Increase your uptime using heavy-duty front and rear frames, hitch and wet disk brakes. Volvo proven durability and the support of extensive warranty options means you never need to worry about getting the job done. Strength and durability are hallmarks of the Volvo articulated hauler.



Fifty years strong

Fifty years and fifty tonnes later, Volvo is the world's leading manufacturer of articulated haulers. We invented the concept and have been developing and building these machines for over 50 years – it has come a long way from its original 10 tonne articulated hauler. With proven success over the years, the machines include innovative technology and the renowned Volvo engine.



Service access

With industry-leading access, servicing your machine is quick and easy. The front grill swings down, opening a service platform with anti-slip steps. The electric hood opens to 90 degrees, allowing full and safe access to the engine compartment.



Volvo dealer network

The exclusive Volvo dealer network is there to support you whenever you need it. Volvo offers a number of services, local knowledge and global experience, including telematics machine monitoring – CareTrack™ and MATRIS™ – as well as superb parts availability.





UPTIME

Get ready to work with the all new A60H. Designed for heavy hauling in severe off-road operation, the machine's long service life, quality, reliability and durability is everything you expect from a Volvo. Hauling is easier and more efficient.



PROFITABILITY

Reduce cost per tonne with a higher payload. The state-of-the-art design allows for more capacity while improving fuel efficiency so you can move more for less.

Move more, make more

Increase your business's profitability by moving more for less. Industry-leading fuel efficiency, innovative technology and vital operational data tools help to optimize production and control your maintenance costs, maximising your return on investment.

Fuel efficiency guarantee

The A60H, powered by the world-renowned Volvo engine, delivers excellent fuel efficiency without compromising on power or performance. With guaranteed fuel efficiency, this machine will increase your profitability and improve your return on investment.



Maximise your investment

Meet your targets faster with the A60H. Increase your earnings with a higher payload and greater productivity for lower cost per tonne.



Control your maintenance costs

The range of Customer Support Agreements offer preventive maintenance, total repairs and a number of uptime services. Volvo uses the latest technology to monitor machine operation and status, giving you advice to increase your profitability. By having a Customer Support Agreement you are in control of your service costs.



Operational data

Receive valuable data to improve onsite efficiency and save costs. With intelligent systems from Volvo such as MATRIS™, CareTrack™ and the On Board Weighing system, you will optimize your production and minimise your operational costs.



Bigger and bolder

Achieve astounding productivity with the A60H. This machine is the ultimate hauler, featuring 100% off-road performance, proven Volvo technology and impressive payload – contributing to sustainable operations, year after year.

Articulated hauler concept

Go where others can't. The A60H embodies the full articulated hauler concept and provides total versatility so you can access the entire jobsite and climb steeper gradients. Work in all seasons, terrains and applications using tailored machine configurations and tires, optimized for this 60 tonne machine.



The best articulated hauler

The ground-breaking A60H is the best articulated hauler on the market and the latest innovation from Volvo. With matched drivetrain, automatic drive combinations including 100% differential locks, all-terrain bogie, hydro-mechanical steering and active suspension, this machine is unbeatable.



Comfort at speed

A60H is fitted with active hydraulic front suspension – permitting high hauling speeds in tough conditions. This optimizes operator comfort and stability during travel. Move more material in a shorter time for unmatched productivity.



Load optimization

The On Board Weighing System guarantees the optimal load every cycle. This maximizes production, boosts fuel efficiency and reduces machine wear in all site conditions and operations.





PRODUCTIVITY

The A60H can move more tonnes per hour and give a 100% in all conditions. The largest articulated hauler on the market has a bigger payload for your application, delivering up to 40% more productivity.

Simply the best and the biggest

PROFITABILITY

The state-of-the-art design allows for more capacity while improving fuel efficiency so you can move more for less.

Fifty years strong

Fifty years and fifty tonnes later, Volvo is the world's leading manufacturer of articulated haulers.

Guaranteed durability

Increase your uptime using heavy-duty front and rear frames, hitch and wet disk brakes.

The best articulated hauler

The ground-breaking A60H is the best articulated hauler on the market and the latest innovation from Volvo.

Maximize your investment

Meet your targets faster. Increase your earnings with higher payload and greater productivity for lower cost per tonne.

PRODUCTIVITY

The A60H can move more tonnes per hour and give a 100% in all conditions.



Load optimization

The On Board Weighing System guarantees the optimal load every cycle.

OPERATOR'S CHOICE

Its comfortable cab and ease of operation, even in adverse conditions, makes operators choose this machine.

Fuel efficiency guarantee

The A60H is powered by the world-renowned Volvo engine delivers excellent fuel efficiency without compromising on power or performance.

Service access

With industry-leading access, servicing your machine is quick and easy.

UPTIME

Designed for heavy hauling in severe off-road operation, its long service life, quality, reliability and durability is everything you expect from a Volvo.

Articulated hauler concept

Go where others can't. The machine embodies the full articulated hauler concept and provides total versatility.





OPERATOR'S CHOICE

When many other machines are onsite, most operators prefer the Volvo. Its comfortable cab and ease of operation, even in adverse conditions, makes operators choose this machine.

The ultimate operating environment

The A60H is the number one operator's choice because of its industry-leading spacious cab and comfortable work environment. Its superior comfort, control, ease of operation and safety appeals to operators, maintaining productivity all day, every day.

Total operator control

Stay in control at all times. The dump support system, dynamic Volvo engine brake and load and dump brake, all help the operator to control the machine for extra productivity and safety.



Ease of operation

The ergonomic, comfortable controls are easy to understand and suit all operators, combined with automatic functions for increased ease of operation.




Operator comfort

Feel comfortable and spend more time in the A60H. The centrally positioned operator, superior steering, excellent suspension, low noise levels, climate control, space and visibility, reduce operator fatigue for more effective operations.



Safety

A number of safety features such as superior visibility and efficient lighting help to keep the operator and people working around the machine safe in the most demanding working environments – whether it's the operator, trainers, mechanics or site workers.



Volvo A60H in detail

Engine

16 liter, 6-cylinder straight turbocharged diesel engine with 4 valves per cylinder, overhead camshaft and electronically controlled unit injectors. The engine has wet replaceable cylinder liners and replaceable valve guides and valve seats.

Engine model	Volvo	D16F
Max power - SAE J1995 Gross	kW	495
	hp	673
at engine speed	r/min	1 800
Flywheel power - ISO 9249, SAE J1349 Net	kW	492
	hp	669
at engine speed	r/min	1 800
Max torque - SAE J1995 Gross	Nm	3 200
Max torque - ISO 9249, SAE J1349 Net	Nm	3 177
at engine speed	r/min	1 050
Displacement	l	16.1

Electrical System

All cables, sockets and pins are identified. Cables are enclosed in plastic conduits and secured to main frame. Halogen lights. Prewired for options. Connectors meet IP67 standard for water-proofing as necessary.

Voltage	V	24
Battery	V	2x12
Battery capacity	Ah	2x225
Alternator	kW/A	2.264/80
Starter motor	kW	9

Drivetrain

Torque converter with built-in lock-up function.
Transmission: Fully automatic Allison planetary transmission with 6 forward gears and 2 reverse gears. Internal torsional damper in the torque converter.
Dropbox: Volvo-developed, in-line design with high ground clearance and 100% longitudinal "dog clutch" type differential lock.
Axles: Heavy duty, purpose built Volvo design with fully floating axle shafts, planetary type hub reductions and 100% dog clutch type diff-lock.
Automatic traction control system (ATC).

Torque converter		1.85:1
Transmission	Volvo	6630 ORS
Dropbox	Volvo	IL3 ATC
Axles	Volvo	AHW80

Suspension

Front suspension: Unique, full hydraulic, with automatic leveling and stabilizer.
Rear suspension: 100% maintenance free. Straddle mounted bogie beam. Independent wheel movement via a 3-point mounting system.

Hydraulic cylinders (struts), front/rear		2/0
Accumulators, oil-nitrogen, high pressure, front		2
Levelling sensors		2

Brake system

Fully hydraulic, wet multiple disc brakes with enclosed, forced oil-cooled multiple discs on all wheels. Two circuit brake system. Complies with ISO 3450 at total machine weight.
Circuit division: One circuit for front axle and one for bogie axles.
Parking brake: Spring-applied disc brake on the propeller shaft, designed to hold a loaded machine on a grade of up to 18%. When the parking brake is applied, the longitudinal differential is locked.
Retarder: Service brake retarder function and Volvo Engine Brake (VEB).

Steering System

Hydro-mechanical articulated steering, self compensating design.
Two double-acting steering cylinders.
Steering angle: 3,4 steering wheel turns lock-to-lock, ±45°.
Steering system, including secondary steering fulfils ISO 5010.

Chassis

Frames: box type, heavy duty. High strength steel, robot welded.
Rotating hitch: 100% maintenance free, fully sealed, with permanently greased tapered roller bearings.

Cab

Mounted on rubber pads. Ergonomically designed. Easy entry and exit. Wide angle forward view.
Operator centrally positioned above the front axle. Adjustable operators seat with retractable seat belt.
Tilt/telescopic steering wheel. Ergonomically positioned controls. Filtered air. Optional climate control system.
Operator communication system: Contronics.
Large color display, user-friendly and easy-to-understand information, all vital machine functions are constantly monitored.
Instructor seat with seat belt.
Safety: ROPS/FOPS standards approved according to ISO3471, SAE J1040 / ISO3449, SAE J231.

Sound level in cab (ISO 6396) - LpA dB(A) 72

External sound level (ISO 6395) - LwA dB(A) 113

External sound level with sound kit: 111 dB(A)

Hydraulic system

Pumps: Five variable displacement piston pumps driven by the flywheel PTO.
One ground-dependent piston pump for secondary steering mounted on the dropbox.
Two return oil filters with magnetic cores provide effective oil filtration.

System max working pressure MPa 28

Dumping System

Patented Load and Dump Brake.
Dumping Cylinders: two single stage double acting cylinders.

Tipping angle ° 70

Tipping time with load s 13

Lowering time s 10

Body

Plate thickness

Front	mm	8
Sides	mm	14
Bottom	mm	16
Chute	mm	16

Material HB400 steel

Yield strength N/mm² 1 000

Tensile strength N/mm² 1 250

Load Capacity

Standard Body

Load capacity	kg	55 000
Body, struck	m ³	25.8
Body, heaped 2:1	m ³	33.6

With overhung tailgate

Body, struck	m ³	26.5
Body, heaped 2:1	m ³	35.1

Specifications

REFILL CAPACITIES

Crankcase	l	55
Fuel tank	l	750
Cooling system	l	75
Brake cooling system	l	131
Transmission	l	58
Dropbox	l	12
Axles, front/bogie	l	74/147
Hydraulic tank	l	198

OPERATING WEIGHT UNLOADED

Tires		33.25R29
Front	kg	22 350
Rear	kg	21 050
Total	kg	43 400
Payload	kg	55 000

Operating weight includes all fluids and operator

TOTAL WEIGHT

Tires		33.25R29
Front	kg	28 700
Rear	kg	69 700
Total	kg	98 400

GROUND PRESSURE

Tires		33.25R29
Unloaded		
Front	kPa	125
Rear	kPa	58
Loaded		
Front	kPa	159
Rear	kPa	193

SPEED

Forward		
1	km/h	6.5
2	km/h	9.7
3	km/h	12.9
4	km/h	19.2
5	km/h	25.9
6	km/h	54.9
Reverse		
1	km/h	5
2	km/h	7.5

Wheel loader PASS MATCHING


	L220	L250	L350
Number of passes			
A60H	6	5	4

	Well matched, 2-4 buckets.
	Loader under capacity, 5 buckets or more.
	Loader undersized for optimum match, reach might be an issue.

Excavator PASS MATCHING

	EC480	EC750	EC950
Number of passes			
A60H	11	7	6

	Well matched, 4-6 buckets.
	Excavator under capacity, 7 buckets or more.
	Excavator undersized for optimum match.



DIMENSIONS

Pos	Unit	A60H
A	mm	12 225
A1	mm	5 872
A2	mm	6 900
B	mm	6 310
C	mm	3 852
C1	mm	1 772
D	mm	3 293
D1	mm	2 986
E	mm	1 440
F	mm	5 050
G	mm	2 140
H	mm	1 743
I	mm	541
J	mm	3 510
K	mm	2 658
L	mm	1 030
M	mm	7 960
N	mm	10 014
N1	mm	4 761

DIMENSIONS

Pos	Unit	A60H
O	mm	3 989
P	mm	3 673
Q	mm	3 370
R	mm	677
R1	mm	778
S	mm	3 126
T	mm	3 734
U	mm	3 833
V	mm	3 010
W	mm	3 884
X	mm	601
X1	mm	727
X2	mm	845
Y	mm	3 010
Z	mm	3 884
a1	°	24.9
a2	°	70
a3	°	45

A60H: Unloaded machine with 33.25R29 tires.

Equipment

STANDARD EQUIPMENT

Engine

Direct injected, electronically controlled, turbocharged, intercooled
Grouped oil filters, for ease of change
Preheater for easier cold starts
VEB (exhaust retarder EPG + compression brake)

Tires

33.25R29
800/80R29

Drivetrain

6x4 and 6x6 automatically engaged drive modes
Dog clutch type 100% diff-locks in all axles
Full automatic transmission
Two-stage dropbox with longitudinal diff-lock
Torque converter with automatic lock-up

Electrical system

80 A alternator
Battery disconnect switch
Extra 24 V socket for lunch cooler
Lights:
Back-up light
Brake lights
Cab lighting
Direction indicators
Headlights
Instrument lighting
Parking lights
Rear lights

Brake System

Hill assist
Load & Dump Brake
Retarder pedal
Parking brake on propeller shaft
Two circuit, fully hydraulic, wet discs on all axles

Body

Body prepared for exhaust heating and optional equipment
On board weighing (OBW)

Safety

Anti-slip steps and platforms
Dump body lock
Handrails on steps and platforms
Hazard lights
Horn
Protective grill for cab rear window
Rear-view mirrors
Retractable 3-inch safety belt
ROPS/ FOPS protected Care Cab
Secondary steering
Steering joint lock
Windshield washers
Windshield wipers with interval function
Dump support system

STANDARD EQUIPMENT

Comfort

ACC control panel
Ashtray
Cab heater with filtered fresh air and defroster
Can holder /storage tray
Cigarette lighter
Instructor seat with seat belt
Overhead console for radio
Sliding window
Space for lunch cooler
Storage box
Sun visor
Tilt/telescopic steering wheel
Tinted glass

Operator information interface

Gauges:
Brake pressure
Fuel
Speedometer
Tachometer
Wet disc brakes cooling oil temperature

Warning lights grouped and easy to read

Central warning (3 levels) for all vital functions

Central positioned information display

Automatic pre-start checks
Clock
Hour meter
Operational information, easy-to-navigate menu
Troubleshooting diagnostics

Exterior

Front mudguard wideners and rear mudflaps

Service and Maintenance

Electrical engine hood and belly plate
Drainage hose
Machine Tracking Information System MATRIS
Service platform integrated in the front grill
Tool box

OPTIONAL EQUIPMENT

Engine

Air pre-cleaner, cyclone type
Air pre-cleaner, oil-bath type
Air filter, heavy duty, EON
Engine heater, 240 V
Engine heater, diesel (Eberspächer)
Engine auto shutdown
Engine shutdown timer
External emergency engine stop
Fuel filter, extra
High engine idle speed

OPTIONAL EQUIPMENT
Electrical system
Headlights, LED
Warning beacon, LED
Working lights, LED
Entrance light
Seat belt indicator, external
Anti-theft system (pin code)
Rear view camera
Reverse alarm
CAN-BUS interface, extra
Cab
Noise reduction kit (fulfils 2000/14/EC)
Anchorage, operator's manual
Cab heating/ventilation timer
Cable kit, for cab heater
HEPA cab air filter
Bluetooth radio kit
Rear view mirrors, adjustable, el.heated
Seat belt XXL, non-retractable
Sun blinds, side windows
Universal key
Air suspended, heated, fully adjustable seat
Armrest for operator seat
Headrest for operator seat
Air blow gun

OPTIONAL EQUIPMENT
Body
Body exhaust heating
Front spillguard, extra
Side extension, light material
Tailgate, overhung, wire-operated
Wear plates
Safety
Fire suppression system
Warning triangle
First aid kit and fire extinguisher
Fire extinguisher
Wheel chocks
Service and Maintenance
Lube system, standard machine
Tool kit
Other
Siberian kit -40°C
Arctic oil kit
CareTrack
Fast fuelling system
Jump start connector, NATO -type

SELECTION OF VOLVO OPTIONAL EQUIPMENT

Rear view camera and monitor



Tailgate




Oil bath pre-cleaner




Fast fuelling



Volvo fire suppression system



Not all products are available in all markets. Under our policy of continuous improvement, we reserve the right to change specifications and design without prior notice. The illustrations do not necessarily show the standard version of the machine.



VOLVO

Volvo Construction Equipment
www.volvoce.com