

730A VHP

Series V

CHAMPION[®]

MOTOR GRADERS



MODEL	730A VHP	736A VHP	730 VHP
Configuration	Articulated	Articulated - All Wheel Drive	Rigid Frame
Operating Weight	37,552 lbs (17 034 kg)	37,972 lbs (17 224kg)	36,432 lbs (16 526 kg)
Net Power – Gears 1-2 – Gears 3-8	180 hp (134 kW) 200 hp (149 kW)	180 hp (134 kW) 200 hp (149 kW)	180 hp (134 kW) 200 hp (149 kW)

730A VHP 736A VHP 730 VHP

SPECIFICATIONS:



BASE OPERATING WEIGHT (Standard Equipment)

Weights shown include full cab with ROPS, all operating fluids and operator.

730A VHP

Total 34,520 lbs. (15 658 kg)
On front wheels 10,415 lbs. (4 724 kg)
On rear wheels 24,105 lbs. (10 934 kg)

736A VHP

Total 34,940 lbs. (15 849 kg)
On front wheels 10,665 lbs. (4 838 kg)
On rear wheels 24,275 lbs. (11 011 kg)

730 VHP

Total 33,400 lbs. (15 150 kg)
On front wheels 10,497 lbs. (4 761 kg)
On rear wheels 22,903 lbs. (10 389 kg)

Weight adjustments for various options are listed.

Typically equipped operating weight: Includes 17.5 x 25, 12 pr., G2 tires on 14" (356 mm) rims, and 14' x 29' x 1" (4 222 mm x 740 mm x 25 mm) moldboard and scarifier.

730A VHP 37,552 lbs. (17 034 kg)

736A VHP 37,972 lbs. (17 224 kg)

730 VHP 36,432 lbs. (16 526 kg)



PRODUCTIVITY (Standard Equipment)

730A

Maximum blade pull
(no wheel slip, 0.9
traction co-efficient) 21,695 lbs. (9 841 kg)
Blade down pressure
- cutting capability
(ISO 7134) 18,113 lbs. (8 216 kg)
Blade down pressure is the maximum downward
force which may be applied at the cutting edge.



ENGINE DATA

Make/Model Cummins 6CT8.3
Type 4 Cycle, Turbocharged, Aftercooled
No. of cylinders In Line 6
Bore & stroke 4.49 x 5.32 in. (114 x 135 mm)
Displacement 504.5 cu. in. (8,27 L)
Rated gross brake horsepower @ 2200 RPM
- Gears Forward, 1, 2 and
Reverse 1 193 hp (144 kW)
- Gears Forward 3-8 and
Reverse 2-4 215 hp (160 kW)
Rated net brake horsepower @ 2200 RPM
- Gears Forward, 1, 2 and
Reverse 1 180 hp (134 kW)
- Gears Forward 3-8 and
Reverse 2-4 200 hp (149 kW)
736A VHP - Rated net brake horsepower, all wheel
drive on, in all gears 200 hp (149 kW)
Torque @ 1500 RPM 542-711 lb-ft. (735-964 N-m)
Torque rise (Net) 24-53%

Engine equipped with a two stage, dual element,
dry-type air cleaner with evacuator and dash-
mounted service indicator, 24 volt starting and
electrical system with 75 amp (1800 watt)
brushless alternator with internal voltage
regulator. Two heavy duty 12 volt maintenance-
free batteries with 625 cold cranking amps (CCA)
and 180 minutes reserve capacity per battery. 900
CCA batteries available optionally. System includes
battery disconnect.

Performance: Rated net brake horsepower SAE standard
J1349/ISO 3046-2 conditions with water pump, lubricating oil
pump, fuel system, air cleaner, muffler, alternator, and cooling fan.



TRANSMISSION

Make/Model Champion 8400
Fully sequential, direct drive, powershift trans-
mission. Engine can not be started if transmission
is in gear. Single lever transmission controller
contains an electronic self-diagnostic feature. The
flywheel-mounted, multi-disc master clutch is oil-
cooled for long life.

Ground speeds at 2200 RPM with standard tires:

Forward		Reverse			
Gears	mph	km/h	Gears	mph	km/h
1	2.7	4.3	1	2.7	4.3
2	3.8	6.1			
3	5.3	8.5	2	5.3	8.5
4	7.4	12.0			
5	10.4	16.7	3	10.4	16.7
6	14.4	23.2			
7	20.2	32.5	4	20.2	32.5
8	27.9	44.9			

Transmission guard is standard equipment and is
hinged for easy access.



DIFFERENTIAL / FINAL DRIVE

Make/Model Champion SR40
Single reduction final drive with an operator
controlled lock/unlock differential. Rear axles are
case hardened, full floating design, supported on
double row spherical roller bearings.



TANDEMS

Oil-tight, oscillating tandem case has internal
gusseting for maximum torsional strength. Field
proven split ring/flanged sleeve tandem mounting
and 1" (25 mm) thick inner wall resists flexing
from side loading during severe applications.
Drive chain sized for long life.

Depth 24.5" (622 mm)
Width 8.25" (210 mm)
Thickness - inner wall 1.0" (25 mm)
- outer wall 0.75" (19 mm)
Center distance 61.5" (1 562 mm)
Drive chain pitch 2.0" (51 mm)
Oscillation ±15°



BRAKES

Service Brakes: Foot Operated
Fade resistant, hydraulically actuated, oil disc
service brakes located at the four (4) tandem drive
wheels are self-adjusting, fully sealed and
maintenance-free. System features cross-over
dual braking circuits for even braking on both
sides of the grader. Includes reserve power assist
and operator warning system (visual and audible).

Parking Brake: Hand Operated

Independent, disc-type hand brake on trans-
mission output shaft and effective on all four (4)
tandem drive wheels. Includes visual and audible
operator warning system for parking brake on,
transmission in gear condition.

Braking systems to:
SAE Recommended Practice J1473 OCT. 90, and J1152
APR. 80; ISO 3450-1993-01-28. Champion uses asbestos-free
brake components.



WHEELS & TIRES (Standard Equipment)

Tire size 14.00 x 24, G-2
Ply rating (pr.) 12
Rim size 10" (254 mm)

Bolt-on rims are interchangeable front and rear on
730 VHP and 730A VHP models.



FRONT AXLE

Type Fully welded steel truss, gusseted for
torsional strength oscillates on a single
3.5" (89 mm) diameter centre pivot pin
Wheel lean - 730/730A VHP 18° R & L
- 736A VHP 15° R & L
Oscillation 16° up and down
Ground clearance 24.0" (610 mm)
Twin 3" (76 mm) diameter wheel lean cylinders
with lock valve are standard equipment.



STEERING

Hydraulic power front wheel steering incorpor-
ating two steering cylinders. Meets SAE J1151
OCT. 90 with optional supplemental steering.

Minimum turning radius using front axle steering,
wheel lean and unlocked differential:

730A VHP articulated frame 25'6" (7 772 mm)
736A VHP articulated frame 24'4" (7 417 mm)
730 VHP conventional frame 35'0" (10 688 mm)
Steering arc 72°
Frame articulation angle 730A/736A VHP 22°
Articulation lock standard.



FRAME

Full front and rear frame sections.

Front: Fully welded box section. Double-lapped in
high load areas. Lowered nose plate on front
frame provides the best visibility in the industry to
the front of the grader.

Minimum dimensions of box section 10.0" x 12.0"
(254 mm x 305 mm)

Plate thickness 0.75" (19 mm)
Vertical section modulus
at arch 163 cu.in. (2 676 cm³)

Linear weight - min-max 104.8-248.8 lbs/ft
(156.0-370.5 kg/m)

Rear: Full rear frame permits modular powertrain
mounting for ease of service and simplifies
attachment mounting.

Minimum dimensions of rear frame 4.0" x 11.0"
(102 mm x 279 mm)

Plate thickness 1.0" (25 mm)

Choice of conventional (rigid) or articulated frames:
730A/736A VHP Articulates behind cab.
730 VHP Conventional
Twin 5" (127 mm) hydraulic cylinders articulate
frame 22° right and left. Anti-drift lock valve
ensures stable operation.



CIRCLE

Hardened teeth, cut on outside of circle for
maximum leverage and minimum wear. Circle is
machined after welding to ensure flatness. The
circle is held positively in place at six points by
three adjustable clamp plates and three adjustable
guide shoes providing optimum circle support and
load distribution. The primary set of clamps and
guide shoes is located at the front of the circle
where greatest loading occurs. DURAMIDE™-
faced clamp and guide shoes prevent metal to
metal contact. DURAMIDE™ is a synthetic material
that extends service life and reduces maintenance
requirements.

Diameter 66.25" (1 683 mm)
Thickness 1.25" (32 mm)
Adjustable guide shoes 3
Adjustable clamp plates 3



CIRCLE DRIVE

Champion's patented dual cylinder circle drive system uses direct-acting hydraulic power for exceptional turning and holding capability under full load. Circle drive system is fully protected against impact damage by an overload cushion valve as standard equipment.

Hydraulic drive cylinders	2
Points of leverage	2
Rotation	360° continuous



DRAWBAR

Fully welded box section. Narrow 'T' design permits optimum visibility to the work area. Drawbar connection provides an adjustment to compensate for different tire sizes. Blade lift cylinder anchors are straddle-mounted on drawbar to provide maximum strength and support.

Dimensions of box section	6.5" x 6.5"
	(165 mm x 165 mm)
Plate thickness	1.0" & 0.75"
	(25 mm & 19 mm)



MOLDBOARD

Standard moldboard with replaceable end bits

12" x 25" x 7/8"
(3 658 mm x 635 mm x 22 mm)

Blade material

SAE 1050 high carbon steel

Edge: through hardened

6" x 5/8"
(152 mm x 16 mm)

boron steel

Drilling - Bolt diameter

6" (152 mm) drilling
- 5/8" (16 mm) bolts

Slide rails supported with DURAMIDE bearings.

BLADE RANGE: MOVEABLE BLADE CONTROL SYSTEM (Standard) (Dimensions shown with standard moldboard)

	LEFT	RIGHT
Reach outside tires - articulated frame	117.0" (2 973 mm)	113.0" (2 870 mm)
Reach outside tires - straight frame	76.0" (1 930 mm)	73.5" (1 867 mm)
Blade slide	26.5" (673 mm)	26.5" (673 mm)
Circle side shift	26.0" (660 mm)	24.0" (610 mm)
Maximum bank sloping angle	90°	90°
Blade ground clearance	17.0" (432 mm)	
Blade cutting depth	30.0" (762 mm)	
Blade tilt range	44° forward	6.5° back

BLADE RANGE: FIXED POINT LIFT SYSTEM (Optional) (Dimensions shown with standard moldboard)

Reach outside tires - articulated frame	105.8" (2 687 mm)
Reach outside tires - straight frame	67.7" (1 720mm)
Blade slide	53.5" (1 359 mm)
Circle side shift	17.2" (437 mm)
Blade ground clearance	17.6" (447 mm)
Blade cutting depth	25.0" (635 mm)
Blade tilt range	44° forward; 6.5° back
Number of moldboard tilt cylinders	2



CAB & CONTROLS

Operator noise exposure is limited to 77 dB(A) per SAE J919 JUNE 86 (enclosed cab). Located in the pedestal head is the engine oil pressure, coolant temperature and fuel level gauges, transmission gear indicator, and a three-level electronic monitoring system. Pedestal located switches include: differential lock/unlock, independent moldboard floats (optional) and combination turn signal, hazard lights, and high beam headlight switch. Heater and wiper/washer controls, lighting and accessory switches are grouped in the operator's right hand console. This console also contains the ignition key and access to the circuit breaker panel. An accelerator/decelerator foot pedal and slider type hand throttle are standard equipment. Cab door opening and closing is easy from either a seated position or while entering and exiting. Fixed front window enhances visibility by reducing window frame width.

Full Height Cab with ROPS INSIDE DIMENSIONS:

Height	74.0" (1 880 mm)
Width @ controls	56.0" (1 422 mm)
Depth @ controls	55.5" (1 410 mm)

An optional Low Profile Cab is available with an inside height of 62" (1 575 mm). All Champion cabs and canopies are designed to meet or exceed SAE J1040 APR. 88, ISO 3471/1-1986(E), and 86/295/EEC ROPS requirements. The seat belt is 3" (76 mm) wide and meets SAE J386 JUNE 93; ISO 6683-1981(E). A cushioned vinyl covered bucket seat with fore & aft and height adjustment is standard.



LOAD SENSING HYDRAULICS

Closed center hydraulic system senses load requirements and maintains system pressure 250 psi (17.25 Bar) above the load pressure.

When hydraulic pressure is not required, system pressure is only 90 psi (6.2 Bar). Low standby pressure improves fuel-efficiency and reduces heat generation.

System incorporates lock valves to prevent cylinder drift under load in the following circuits: blade lift, moldboard tilt, circle shift, wheel lean, articulation and scarifier. All hoses and fittings are equipped with 'O' ring seals to eliminate leaks.

Pump design features include cast iron end covers and center housing, and a one-piece gear and shaft assembly to ensure reliability and a long service life.

Maximum pressure	2,500 psi (172 Bar)
Output at 2200 RPM	0-50.5 gpm (0-191 lpm)
Filtration	7 micron spin-on type



CAPACITIES

	U.S. Gal.	Imp. Gal.	Litres
Fuel Tank	100.0	83.3	378.5
Transmission	10.2	8.5	38.8
Final drive	6.0	5.0	23.0
Tandems (ea.)	26.4	22.0	100.0
Hydraulic oil tank	23.8	19.8	90.0
AWD hydraulic oil (736A VHP)	10.0	8.3	37.9
Coolant Antifreeze protection to -58° F (-50° C)	11.9	9.9	45.0
Engine oil	5.9	4.9	22.4



ALL WHEEL DRIVE - 736A VHP

Completely independent from the main hydraulic system, Champion's All Wheel Drive system incorporates a variable displacement, load sensing piston pump, and a separate reservoir, oil cooler and filter. This allows the system to operate continuously without overheating, and eliminates potential fluid cross-contamination. Champion's AWD design automatically adjusts hydraulic flow and pressure to the drive system to match ground speed and tractive conditions. A positive on/off control allows the operator to concentrate on the task at hand, rather than trying to find the 'correct' AWD setting. No electronics or wheel speed sensors are used. The powered front axle has two variable displacement piston motors with double reduction planetary torque hubs.

Maximum system pressure	3,500 psi (241 Bar)
Stand-by pressure	175 psi (12 Bar)
Filtration	7 micron
Top speed	20.2 mph (32.5 km/h)

STANDARD FEATURES:

- Operator controlled, lock/unlock differential final drive
- 4-wheel, cross-over, dual braking system with reserve power assist
- Ratchet-type park brake with operator warning alarm and indicator
- Fully-sequential, powershift 8400 transmission, with guard
- 13.5" (343 mm) diameter, 4-plate, full oil clutch for operator control
- Choice of rigid or articulating frames
- Full front and rear frame sections designed to absorb shock loading of attachment use
- Cab halogen headlights with dimmer includes directional and hazard lights
- Cushion valve circle drive protection to minimize impact damage
- Hardened circle teeth cut on outside of circle for maximum wear resistance
- Isolation-mounted cab, transmission and engine for reduced noise and vibration
- Adjustable steering pedestal with tilt head for maximum operator comfort
- Gauges include: coolant temperature, engine oil pressure, fuel, hourmeter, dash-mounted air cleaner service indicator, articulation angle indicator, three-level electronic monitoring system - M4 - with visual and audible warnings
- Load-sensing, closed-center hydraulic system with short-throw, low effort control levers, positioned in the industry-accepted arrangement. Hydraulically operated blade lift, circle turn, moldboard slide and tilt, circle shift and wheel lean functions.

• 100 gallon fuel capacity

• Horn

• Hinged radiator guard for easy trash clean out. Engine compartment fan guard included.


• Back-up alarm with automatic volume level

• Painted Champion Yellow, cab painted grey

• Lockable tool box with storage space for scarifier shanks

OPTIONAL EQUIPMENT (May vary)

	lbs.	kg		lbs.	kg		lbs.	kg
Accumulators - blade lift (2)	130	59	- clearance lights front & rear	2	1	Paint - custom colors	-	-
- circle side shift	65	29	- front-mounted plow lights - 2			Radiator shutters - hinged	10	4
Air conditioner - 21,500 BTU			- high	120	54	Reflectors - rear	-	-
- HFC-134a (non-CFC refrigerant)			- low	100	45	Remote valve for attachments		
with cab pressurizer/filter	130	59	- Headlights with dimmer switch	-	-	- 3 or 5 bank - remote mount	25	11
Brush guards	40	18	- Moldboard lights - 2	2	1	Supplemental steering (power		
Cab			- Rear flood lights - 2	2	1	assisted) meets SAE J53 OCT. 84	61	28
- canopy shell with ROPS - deduct (200)	(91)		- Snow wing lights - 2	2	1	Suspension seat	55	25
- FOPS protection for ROPS cab	220	100	Machine Monitor Plus package - M44			Tie-down brackets	100	45
- low profile cab with ROPS - deduct (200)	(91)		Audible and visual warnings for transmission			Tires		
Cab heater - 49,000 BTU	30	14	and hydraulic filter restriction, low engine oil			- 14.00 x 24, 12 pr., G2,		
Cab pressurizer/filter	14	6	pressure, high coolant temperature, high			10" (254 mm) multi-piece rims	360	161
Defroster fan	3	1	transmission temperature, and low			- 17.5 x 25, 12 pr., G2,		
Engine block heater	3	1	transmission clutch pressure	-	-	14" (356 mm) rims	942	428
Engine precleaner - Turbo II	6	3	Mirrors - outside - right	2	1	Tire chains - pair	300	136
Engine side panels	50	23	- left	2	1	Tool kit	-	-
Ether cold start	10	4	Moldboards			Transmission sump heater	-	-
Exhaust rain cap	-	-	- 14' x 25" x 7/8"			Tropical protection	-	-
Fan - blower type (suction type is standard) -	-	-	(4 267 mm x 635 mm x 22 mm)	280	127	Vandalism protection	8	4
First user lifetime frame warranty	-	-	- 12' x 29" x 1"			Wheel weights front or rear - each	250	113
Fixed point lift system - deduct	(560)	(254)	(3 658 mm x 737 mm x 25 mm)	340	154	Window - opening - lower front	-	-
Float control - Right and Left			- 13' x 29" x 1"			Window - opening sliders - left/right	-	-
independent, electric	15	7	(3 962 mm x 737 mm x 25 mm)	490	222	Wiper and washer - front	-	-
Hub odometer	-	-	- 14' x 29" x 1"			Wiper and washer - rear	-	-
Hydraulic tank heater	3	1	(4 267 mm x 737 mm x 25 mm)	640	290	Wiper and washer - lower front windows	-	-
Jack - 20 ton (18.5 tonne)	35	16	Moldboard extensions R & L					
Lights			- 2' (610 mm)	200	91			
- back-up lights - 2	-	-	Moldboard edges -Carbide 3/4" x 5"	-	-			
- beacon (amber or blue)	4	2	Operator convenience package					
			- lunch box, steel vacuum bottle					
			and holder, ash tray	10	5			



DIMENSIONS

A Overall length	27'10" (8 484 mm)
B Overall width	8'4" (2 540 mm)
C Overall height with cab	11'2" (3 404 mm)
- with Low Profile Cab	10'2" (3 099 mm)
D Wheelbase	20'0" (6 096 mm)
E Tread width	6'10" (2 083 mm)
F Blade base	
- ISO 7134	8'6" (2 591 mm)

CHAMPION MATCHED ATTACHMENTS

A-Frame	850 lbs. (386 kg)	Push block	1,050 lbs. (476 kg)	V plow	
Dozer blade		Ripper-scarifier, rear	2,100 lbs. (953 kg)	- 9' (2 743 mm)	2,560 lbs. (1 161 kg)
- 8' (2 438 mm)	1,600 lbs. (726 kg)	Scarifier, front, with 11 teeth	1,450 lbs. (657 kg)	- 10' (3 048 mm)	2,720 lbs. (1 234 kg)
- 9' (2 743 mm)	1,650 lbs. (749 kg)	Snow wing		Windrow eliminator	1,300 lbs. (590 kg)
One-way plow	2,350 lbs. (1 067 kg)	- front-mounted	2,900 lbs. (1 317 kg)		
		- rear-mounted	3,100 lbs. (1 407 kg)		

Specifications subject to change without notice. Some items included in this brochure are optional.
 DURAMIDE is a registered trademark of Champion Road Machinery Limited.
 Your safety and the safety of those around you depends on using care and judgement when operating and servicing your grader. Do not operate the grader until you read and understand the warnings and instructions in the operator's manual.

CHAMPION[®]
MOTOR GRADERS

CANADA
 Goderich, Ont.

© 1997 Champion Road Machinery Limited