

# INGERSOLL-RAND®

## MW-250C Pavement Milling Machine for Asphalt and Concrete



### STANDARD FEATURES

- 31,400 lbs. (14245 kg) operating weight.
- 140 hp (104 kW) turbocharged diesel engine.
- One year, 1000 hour warranty.
- Depth of cut up to 6 inches (152 mm).
- 30 inches (762 mm) cutting width.
- Flush side clearance.
- Angled moldboard for windrowing material.
- Milling speed from 0-120 ft/min (0-37 m/min).
- Maximum travel speed 8.9 mph (14.3 km/hr).
- 4-wheel hydrostatic drive; solid rubber tires.
- 72 inch (1830 mm) turning radius.
- Spring-Applied, Hydraulically-Released secondary/parking brakes.
- Hydraulically driven, front loading conveyor aids production and minimizes clean-up.
- Cam Flex conveyor belt with sidewall means less spillage of material.
- Dual electrically-actuated hydromechanical sensors adjustable from operator's deck and ground.
- Pressurized water system with twin pumps and volumetric control.
- 150 gallon (568 liters) water tank with large water fill opening and basket strainer.
- Efficient, comfortable operator's station accessible from either side.
- Standard instruments include tachometer, hour meter, voltmeter, propulsion charge and system pressure gauge, cutter charge and system pressure gauge, conveyor system pressure gauge and engine temperature and oil pressure gauges.
- Instrument panel has lockable vandalism protection cover.
- Pin locator type tool holder for quick and accurate replacement.
- Large doors for excellent access to all service points; cutter drum access door opens hydraulically.
- 46 gallon (174 liter) fuel tank.
- Optional equipment includes ROPS, lights, tool kit.