

M-450

GRAVITY-FED ASPHALT PAVER

STANDARD FEATURES:

- * NEW unique cable-free hydraulically actuated steering
- * 6 ton hopper capacity
- * 8-12 foot standard paving widths
- * Powerful 26 HP watercooled diesel engine
- * Blaw-Knox Xtend-a-Screed® with full screeded extensions and bolt-on screed plates
- * Gravity-fed material delivery system
- * Blaw-Knox Softprint® track system
- * Bearing-free depth adjustment jacks
- * Dual cylinder hydraulic screed lift
- * User-friendly design



Built Tough and Easily Transported! The Perfect Compact Paver for Driveways.

Length	101"
Height	62"
Width (closed)	101"
Width (open)	109"
Weight	7,000 lbs
Hopper Capacity	5 tons
Track System (length)	49"
Track System (width)	15"
Screed (length)	96"
Screed (width)	15"
Center of Tracks	65"
Transport Width	101"

Engine: 26hp watercooled diesel engine / electric start & stop / alternator and indicator light panel / auto shutdown.

Drive System: Heavy duty servo actuated hydrostatic transmissions w/

auxiliary pump / two fully enclosed heavy duty, self-contained planetary gear boxes / positive direct drive system / two independent, variable speed, hydraulically powered 15" x 49" steel track systems.

Hydraulic Capacity: 25 gallons

Steering: Two independently operated forward / neutral / reverse-type steering levers / hydraulically controlled speed control lever / engine throttle control knob / tracking degree controls.

Xtend-A-Screed: Free floating 96" x 15" screed / independently operated hydraulic extensions extending 2 feet on left and right sides / hydraulically



for more information call 1-800-241-4411

M-450 Asphalt Paver Specifications



The Blaw-Knox M-450's low profile gives the operator full view of the hopper and surrounding areas.



The M-450's compact size gives the operator convenient control over all of the pavers functions.

lifted by two 3" cylinders mounted on sides of paver / propane heated w/ two burners / vibratory system is standard operating at 3600 vibrations per minute.

Augers: Two independently operated 8" augers w/ forward and reverse / mounted on the extensions.

Material Delivery: 6 ton capacity / gravity fed with 1/2" reinforced steel bed / lifted with two heavy duty hydraulic cylinders

Paving Depth: 0-6" / manually adjustable with two bearing free screed jacks.

Basic Paving Widths: 8 to 12' / 4 to 6' standard paving widths.

Speed: Infinitely variable from 0 to 120 feet per minute.

Main Control System: Two operator stations: Primary station (left side) controls for operation include: steering, speed control, throttle, left/right tracking selection, tracking degree, hopper lift, hopper doors, screed lift, screed extensions, vibratory screed, augers, wash-down and horn. Secondary station (right side) controls include: steering, right screed extension, hopper lift and right auger.

Washdown System: One wand with spray nozzle and hose.

Options: cut-off plates



840 Old Bremen Road
Carrollton, GA 30117
(770) 832-1192 • FAX (770) 834-6557
Toll Free 1-800-241-4411

Visit Us On The World Wide Web!

www.ircmg.com