



DD-132HF

Large Asphalt Compactors



*Moving the
World Forward*

Accelerate your productivity

The Ingersoll Rand DD-132HF is a 13.5-tonnes, 84-inch drum, dual-amplitude, high-frequency asphalt compactor. The high-frequency design allows for faster rolling speeds to deliver maximum productivity and keep up with today's faster paving speeds. Dual amplitude allows the operator to easily select between high amplitude for thick lift jobs and low amplitude for light overlay work.

MODEL	DD-132HF
MACHINE WEIGHTS W/ ROPS / FOPS	
Operating Weight (CECE) – lb (kg)	30,325 (13752)
Weight @ Front Drum – lb (kg)	15,880 (7202)
Weight @ Rear Drum – lb (kg)	14,445 (6550)
Shipping Weight – lb (kg)	28,728 (13028)
MACHINE DIMENSIONS	
Length – in (mm)	236 (5995)
Width – in (mm)	92 (2337)
Height – Top Of Steering Wheel – in (mm)	93.8 (2382)
Height – Top Of ROPS / FOPS – in (mm)	125.2 (3179)
Drum Base – in (mm)	139.8 (3550)
Curb Clearance – in (mm)	20 (509)
Inside Turning Radius (to drum edge) – in (mm)	179.6 (4562)
DRUM	
Width – in (mm)	84 (2135)
Diameter – in (mm)	55.1 (1400)
Shell Thickness (nominal) – in (mm)	0.78 (20)
Finish	Machined surface; chamfered & radiused edges
VIBRATION	
Frequency – vpm (Hz)	High 4,000 (66.7) Low 2,700 (45)
Nominal Amplitude – in (mm)	High 0.035 (0.88) Low 0.014 (0.35)
Centrifugal Force – lb (kN)	High 41,720 (185.6) Low 36,680 (163.2)
PROPULSION	
Type	Closed-loop hydrostatic, parallel circuit to both drums
Drum Drive	Heavy-duty radial piston LSHT motors; 2-speed rear motor
Travel Speed Range – mph (km/h)	0 – 6.2 (0 – 9.9)
Compaction Speed Range – mph (km/h)	0 – 4.6 (0 – 7.5)
ENGINE	
Make / Model	Cummins QSB5.9-155
Engine Type	Turbocharged & charge air-cooled 6-cylinder
Rated Power @ 2,200 rpm – hp (kW)	155 (116)
Electrical	12 V DC, negative ground; 95 A alternator
BRAKES	
Service	Dynamic hydrostatic through propulsion system
Parking / Secondary	SAHR on front-drum & rear-drum drive motors
WATER SYSTEM	
Type	Pressure spray drum wetting system with LDPE water tanks
Pumps	Diaphragm water pumps, primary & secondary for each drum
Spray Bars	Primary & secondary spray bars for each drum
Nozzles	Hand-serviceable fan spray nozzles; 12 per spray bar
Filtration	Sock strainer each tank, primary water filter each pump; fine filter each nozzle
Drum Wipers	Front & rear rubber wipers for each drum
Water Tank Capacity – gal (L)	328 (1241)
MISCELLANEOUS	
Articulation Angle (center pivot steering)	+ / - 35°
Oscillation Angle	+ / - 10°
Fuel Tank Capacity – gal (L)	68.4 (259)
Hydraulic Oil Capacity – gal (L)	32 (121.1)
Gradeability (theoretical)	32%

Product improvement is a continuing goal at Ingersoll Rand. Designs and specifications are subject to change without notice or obligation.



OPERATING COMFORT AND CONTROL

Ergonomic design of switches and controls promotes smooth and efficient operation. Lighted instrumentation makes evening and nighttime work easier.

Swivel console places controls within optimum reach. As part of the operator platform, a 5-position swivel console optimizes operator performance.



PERFORMANCE FEATURES

- Complete access to engine compartment through rear-hinged, 1-piece composite engine hood
- Exclusive machined drums with chamfered, radiused drum edges minimize drum edge marking
- High-frequency vibration system of 4,000 vpm offers faster rolling speeds for increased production
- Industry-leading amplitude on high-frequency model for compaction on thicker lifts or stiffer mix designs
- ONE METER BY ONE METER visibility around the unit
- Patented Impact Spacing Meter provides operator with a visual reference for speed control to maintain proper impact spacing, resulting in consistent smoothness
- Premium shock- and vibration-isolated operator platform and ROPS / FOPS, with 5-position swivel console
- ROPS / FOPS support legs positioned for unobstructed side visibility
- SMART start drum vibration system — vibration initiates with lead drum, followed by trailing drum for compaction efficiency
- Superior drum spray system to maintain maximum productivity
 - 12 spray nozzles on each spray bar, more closely spaced for better drum coverage
 - Dual drum wipers as standard equipment
 - Independent primary and secondary spray systems
 - Variable waterflow control to conserve water

AVAILABLE OPTIONS

- Back-up alarm
- Cocoa mats
- Engine air pre-cleaner
- Engine grid heater
- Front and rear halogen work lights
- Fuel strainer
- High Intensity Discharge (HID) lighting with drum edge lighting
- Infrared pavement surface temperature sensor
- Maintenance package
- Strobe light
- Urethane wipers
- Winterization kit



(877) IR BRAND • ingersollrand.com

© 2007 Ingersoll-Rand Company 15-0024