



HT-250 & HT-540

Tack Distributors



*Moving the
World Forward*

Productivity, durability, and safety

The HT-250 and HT-540 tack distributors feature industry-leading technologies to increase productivity and efficiency. The automatic thermostat and ignition reduce heating system monitoring while the flush and recovery system reduces clean-up time. Designed for durability with 10-gauge platform materials, the HT-250 and HT-540 also promote safety through an added propane fuel shutoff to protect from fume buildup.

MODEL	HT-250	HT-540
DIMENSIONS		
Length – in (mm)	120 (3048)	184 (4674)
Width – in (mm)	81 (2057)	76 (1930)
Height – in (mm)	80 (2032)	74 (1880)
Weight – lb (kg)	1,620 (734.8)	2,400 (1089)
Capacity – gal (L)	250 (946)	540 (2044)
TRAILER		
Axles	Single	Dual
Rated Weight – lb (kg)	3,500 (1588)	5,200 (2359) each
Wheels – in (mm)	15 (381)	15 (381)
Brakes	Electric	Electric
Hitch	2" ball	2-5/16" ball
Jack	Yes	Yes
Lighting System	Yes	Yes
ENGINE		
Make	Briggs & Stratton	Briggs & Stratton
Rated Power – hp (kW)	6.5 (4.8)	16 (11.9)
Electronic Start	Yes	Yes
PUMP SYSTEM		
Drive	Gear-reduced	Hydrostatic pump
Pump Diameter – in (mm)	1 (25.4)	2 (50.8)
Output – gpm (L/min)	4 – 10 (15 – 37.9)	0 – 50 (0 – 189)
Spray System	5' wand, 30' hose	5' wand, 30' hose
Flush System – gal (L)	7 (26.5)	7 (26.5)
HEATING SYSTEM		
Burner – BTU	200,000	200,000
Temp Control	50° – 300° F (10° – 149° C)	50° – 300° F (10° – 149° C)
Propane Tank – gal (L)	5 (18.9)	Not included
OPTIONAL EQUIPMENT		
Pintle Hitch	Yes	Yes
6' Distributor Bar	Yes	—
8' Distributor Bar	—	Yes
10' Distributor Bar	—	Yes

Product improvement is a continuing goal at Ingersoll Rand. Designs and specifications are subject to change without notice or obligation.



HT-250 PERFORMANCE FEATURES

- Compact design for easy transportation and maneuverability in light-duty applications
- Gear-reduced drive with 1" material pump
- Reliable 6.5 hp engine
- Tank capacity of 250 gallons

HT-540 PERFORMANCE FEATURES

- High performance features help contractors complete larger jobs with maximum efficiency
- Hydrostatic drive and 2" material pump
- Large tank capacity of 540 gallons
- Powerful 16 hp engine
- Dual-axle design



HYDROSTATIC PUMP CONTROL

The hydrostatic drive on the HT-540 allows variable volume flow through the robust 2" material pump, providing unparalleled efficiency to fit any size application.



THERMOSTAT AND IGNITION

Electronically controlled, the 200,000 BTU propane heating system automatically maintains desired heat setting.



FLUSH AND RECOVERY SYSTEM

Integrated solvent and recovery tanks permit quick and easy cleaning of pump, plumbing, hose, and handwand.



(877) IR BRAND • ingersollrand.com

© 2006 Ingersoll-Rand Company 20-0003