
ECR18E

Volvo Compact Excavators 1.7-1.98 t 16.3 hp







Ready for work

The ultra-short swing radius ECR18E is the perfect choice for working in tight conditions. Easy to transport and easy to operate, this 1.8t excavator will make light work of tough jobs. With a robust design, combined with best-in-class service access, you can be sure this is a machine designed to promote low operating costs.

Small but tough

The unique high-profile counterweight design is made from three strong pieces of cast iron which wrap around the rear of the machine, protecting all vital components. All-around steel panels, recessed 10mm from the counterweight, offer further protection.



Safe and easy operation

The roomy and uncluttered operator environment of the machine is designed to keep you safe and focused while at work, including simple layout of the controls, fingertip controls and large travel pedals. Safety is built-in to the machine with a ROPS/TOPS/FOPS canopy, a large entrance including high visibility step, and an orange seatbelt as standard for easy checks by site managers.



Best-in-class serviceability


Complete maintenance tasks with speed thanks to the hinged fuel tank which enables an impressive ease of access to the engine compartment, and easy to locate daily check points. A 50-hour greasing interval further contributes towards the best-in-class serviceability of this machine.



Transport with ease

Transportation of the machine is safe and secure, thanks to its light weight and convenient design. With automatic slew lock and four easily accessed large tie-down points on the upper frame, the machine can be safely transported on a small trailer with up to three buckets and a hydraulic breaker, while maintaining a total transport weight of less than 2t.





COMPACT BY DESIGN

For superior versatility when working in confined spaces, the ECR18E features an ultra-short tail radius. The machine design ensures that the frame corner, swing post and cylinder stay within the tracks when digging alongside obstacles. The result is maximum visibility and a reduced risk of machine damage when working in tight conditions.

Short swing, big potential

SAFETY FIRST

- High visibility entry step, orange seatbelt A VOLVO EXCLUSIVE
- Controls lock options (switch, seat operator presence or buckled seatbelt sensor)

A VOLVO EXCLUSIVE

- 4 large easily accessible tie-down points on the upper frame **NEW**
- Outstanding all-around stability
- ROPS/TOPS/FOPS certified 4-pillar canopy

SMALL BUT TOUGH

- All-around steel panels **NEW**
- High-profile cast counterweight A VOLVO EXCLUSIVE
- Boom cylinder on top
- Protected hoses, routed inside the boom
- Steel tracks

OPERATE WITH EASE

- Fingertip controls A VOLVO EXCLUSIVE
- Simple controls layout
- Uncluttered floor, large travel pedals
- Automatic 2-speed travel
- Smooth combined movements



COMPACT BY DESIGN

- Ultra-short swing radius **NEW**
- Variable undercarriage width, less than 1-meter wide
- In-track boom swing



MAXIMIZE PROFITABILITY

- Best-in-class access to engine compartment thanks to hinged fuel tank **A VOLVO EXCLUSIVE**
- Auto engine shutdown and auto-idle (options) **A VOLVO EXCLUSIVE**
- 50-hour greasing intervals

THE COMPLETE PACKAGE

- Genuine Volvo Parts
- Full range of matched Volvo Attachments

Specifications

ECR18E		
Engine		D0.9A
Gross power	kW	12
Net power	kW	11.2
at engine speed	r/min	2 300
Operating weight	kg	
Operating weight - canopy version	kg	1700
Bucket capacity	m³	0.014 - 0.051
Travel speed	km/h	1.8 / 3.5
Slewing speed	r/min	9.5
Breakout force	kN	12.9
Tear out force (arm breakout force)	kN	7.95
Overall width	mm	995/1352
Overall length	mm	3 431
Main hydraulic pump max. flow	l/min	34
Boom swing angle, left / right	0	

